



X



Projector
Screen.com.hk

投影產品專門店



TABLE OF CONTENTS

電動地升幕	2
VIVIDSTORM S-ALR 常規/長焦 抗光灰幕 電動地升幕 黑色機箱 (16:9)	2
VIVIDSTORM S-WC 常規/長焦 電動地升幕 白幕/黑邊/黑色機箱 (16:9)	14
快速折疊幕	32
AOV 4:3 快速折疊幕 多尺寸選擇 (Quick Folding Screen)	32



電動地升幕




適合常規/長焦投影機 抗光灰幕系列




灰幕抗光・電動地升幕

適合常規/長焦投影機



Black Housing Classic works



S Electric Tab-Tension Floor Screen Obsidian Long Throw Ambient Light Rejecting Enjoy Your 4K HD Home Theater

A Projection Screen That Rises From The Ground

Open your home theater easily. The screen, which rises from the ground, is not only convenient for activities, but also does not need to be installed through holes in the wall.



No Longer Afraid Of The Day Or The Light

No hole, no installation, portable and mobile.



Enjoy your 3D visuals in HD home theater S Electric Tab-Tension Floor Screen 3D Obsidian Long Throw Ambient Light Rejecting

Imported Light Resistant Screen

Anti light upgrade. In the ambient light has a weakening effect, so that you can watch movies in the daytime.




No Drilling Is Required

You don't need to drill holes in the wall or floor to use the screen, but make sure it's placed on a flat surface.

Wrinkles Free

Screen with fabric design, plus metal strong support, better stretch the screen, prevent curling and other phenomena.



3D View More Wonderful

The screen supports the projection of 3D images, making the family view more wonderful.



Assemble Brand Motor

Smooth operation at the motor, silent and stable

DC power supply
DC power supply, energy saving
and environmental protection


Ultra quiet design
The world's leading silent patent
technology, vertical ultra silent
structure design, ultra silent
operation, noise as low as 20dB

Limit adjustment
Precise limit structure, adjust
the ideal height


Overheating protection
Overheated automatic power-off
to ensure the safety and
health of the motor

4K HD Visual Feast

Support 4K ultra high definition projection
to build luxury HD home theater



1080P 4K UHD



Panoramic View

Multiple people share a 150° HD view, no
matter where they sit. Enjoy the same clear,
gorgeous 4K HD picture

PRODUCT DETAILS



Screen Cable
This screen is designed with the ability to
extend the screen cable to meet the
screen and prevent pulling and shaking



Electric Ground Lift
One touch and lift



Aluminum Alloy Top Cover
Bright and firm



Tension Bracket
Strong support force




Adjustable Fixed Base
Steady and safe




Black Housing
Classic works



White Housing
Pure fashion



White Housing
Pure fashion



Important Reminder

Due to the large size of the anti light curtain, please measure the elevator and corridor of your home before purchase. For
the moment, only elevator direct delivery is supported, not corridor delivery. If the elevator cannot reach the destination, the
delivery will be delivered to the elevators, and you can arrange the transportation by yourself. You can negotiate with the
express delivery or handle the extra stair handling costs (please contact customer service for details).

Custom Service

If you need to customize the curtain of special
size, please contact the online customer service.
After the price is determined, we will make it for
you as soon as possible!

Warm tips, if you mind the following conditions do not purchase! ! ! !

1. When there are a few black spots, white spots, stains and other impurities on the
screen surface, but if they are qualified according to the detection method, then such situ-
ation is not a product quality problem, and it is within the scope of product qualification.




Figure 1 side view





Figure 2 top view

The detection method is as follows:

- Please raise the screen of this product and close to the wall, and the observer can observe the film at a distance of 5 meters away from the screen;
- The observer needs to observe the shadow in the normal light environment (illumination 500-600lx);
- The distance between the observer and the front of the screen should be kept at a distance of 3 meters, and the center point of the screen should be close to or higher than the horizontal line of sight (as shown in Figure 1), and the observation should be made at the center point, 1m to the left and 1m to the right (as shown in Fig. 2).


As long as the test results of the product are within the allowable range, the product is qualified.



- The white screen is listed as the quality standard because it is not only the reflection surface of the projector image (the black surface is observed from the upper and lower direction, and the white surface is observed from the bottom direction), but also the main function surface of the viewing image, so the white screen is listed as the quality standard. It should be noted that if the white screen surface does not exceed the quality specification, it will be regarded as meeting the factory qualification standard.
- Different from the white screen, the black screen is used as a functional surface to absorb indoor ambient light. In view of the fact that there is no direct correlation between the black screen surface and the image viewing quality, its quality specifications are quite different from that of the white surface. It should be noted that the slight black marks on the black screen surface are inevitable appearance phenomena in the production process of industrial products, which meet the factory qualification standard.

Conclusion: it should be noted that the slight black marks and white spots on the black screen surface of the anti light projection screen products are normal product appearance phenomena, which will never affect the image viewing quality. Please use it at ease.


- If there are regular creases on the screen surface after the screen is opened, don't worry. This is a normal phenomenon. It is caused by the screen being curled and tightened for a long time, which does not affect the user's viewing. After opening the screen for a period of time, you will notice that the stripes on the screen will gradually disappear.



3 Please note that when placing this product, please make sure that the product is always in a horizontal state.


Do not place the screen in an inclined or vertical position.

4 After using for a period of time, if the cover on both ends of the screen is slightly tilted, there is no need to worry. This is a normal phenomenon and does not affect the viewing and use. In addition, due to the cover warping, there is a gap between the screen and the housing case after closing, which is also a normal phenomenon.



Please make sure the product is placed horizontally

There was a slight tilt after the screen was closed



無“升”有

一鍵開啟
可收納隱藏的巨幕



VIVIDSTORM S ALR 電動地平屏/長焦抗光幕

一鍵開啟你的次世代影院

免打孔設計 折箱插電即用

你不需要在牆上或地板上打孔來安裝屏幕
包裝裡會送它放在一個平面的平面



全新的觀影體驗



精彩的3D效果

在家也能享受影院級3D影像

進口抗光幕布
拒絕環境光干擾，讓家庭影院不分晝夜，白天也能享受清晰影像。

白天/光線環境對比

傳統幕面

白天/光線環境對比

高亮抗光幕

幕平如鏡
幕面採用拉線設計，完美的呈現原始畫面，幕面無曲線變位。

拉線工藝，沒有更多的褶皺

盡收眼底，引人入勝
屏幕可視尺寸：72"-150"

產品詳情

拉線工藝
幕面採用拉線設計，拉線幕面更平整，觀感更清晰，防止捲曲變形等現象。

電動升降
方便收納

紙合金頂蓋
堅固耐用

雙V型支撐系統
防止變形，確保平整

可旋轉固定底座
更平穩的升降更安心

皆“大”歡喜
全場運動，聲息無聞，150度無死角，全景大視角。

黑色機箱
經典款

幕面尺寸 (單位: mm)

幕面尺寸 (單位: mm)

幕面尺寸 (單位: mm)

幕面尺寸 (單位: mm)

幕面尺寸 (單位: mm)

幕面尺寸 (單位: mm)

VIVIDSTORM S-ALR 常規/長焦 抗光灰幕 電動地升幕 黑色機箱 (16:9)

- 抗光幕布材質，推薦用於普通/標準/長焦投影機使用
- 在弱光環境下表現出色- 建議投影機具有2200ANSI 或更高的真實流明
- 電動升降-收放自如，不佔空間
- 雙彈簧V型支架系統，幕面緊繃平直
- 0.8增益，150°視不挑角度，兼容3D/4K/8K高清視覺盛宴
- 多種控制方式實現上下約20-30秒！無線遙控
- 即插即用，快速安裝，無需鑽孔安裝，節省空間的設計
- 72吋-200吋可選擇 (因尺寸及重量限制，超過120吋只能送貨到樓下；72吋至120吋需要客人確認樓宇電梯能放入投影幕，及運送到指定樓層，才能安排送貨上門)
- 品牌靜音管狀電機

支援常規/長焦投影機，進口抗光幕布，支援4K投影效果，高對比度，高度還完色彩，一鍵升降，帶遙控

(如需白色機箱款，或需要135吋以上，請聯絡本店查詢 3188 4814)

VIVIDSTORM 所有專業投影幕一覽表

恭喜 **香港投影** 成為

VIVID STORM

專業投影幕

香港地區特約代理商




VIVIDSTORM
S ALR 電動地升 常規/長焦抗光幕
一鍵開啟你的次世代影院

更大的屏幕，更大的尺寸

屏幕尺寸：72"- 150"

根據空間大小/個人喜好
選擇合適的屏幕尺寸，
讓觀看更舒適。



推薦觀看距離：至少2.5米



全新的觀影體驗



電動升降
收放自如



無線遙控
遠程控制



150°視角
全方位顯示



護眼技術
呵護視力健康



72吋-150吋
更多尺寸選擇



品牌電機
靜音驅動

無中“升”有

一鍵開啟
可收納隱藏的巨幕



屏幕打開



屏幕关上



免打孔設計 拆箱插電即用

你不需要在牆上或地板上打孔來安裝屏幕
但要確保它放在一個平坦的平面

幕平如鏡

幕面采用拉線設計，完美的呈現原始畫面，幕面無曲線波紋。



拉線工藝，沒有更多的褶皺

進口抗光幕布


拒絕環境光干擾，讓家庭影院不分晝夜
白天也能享受清晰影像



傳統幕面



高清抗光幕



盡收眼底，引人入勝

屏幕可選購尺寸：72"-150"



精彩的3D效果

在家也能享受影院級3D影像



裝配品牌電機

奧科同步靜音管狀電機,運行流暢

☑ 直流供電

直流供電, 節能環保

☑ 靜音設計

領先的靜音專利技術, 斜齒超靜音結構設計; 實現運行噪音低至30dB的靜音效果

☑ 限位調節


精準限位結構, 調節理想高度

☑ 過熱保護

過熱自動斷電保護, 保障電機安全健康

4K高清視覺盛宴

屏幕支持4K投影(主要以投影機畫面質量為主)
暢享高清視覺盛宴





皆“大”歡喜

全家總動員，聚會無限制，150度無死角，
全景大視角。

產品詳情



拉線工藝

屏幕搭配拉線設計，拉伸幕面更好的保證
幕面平整，防止捲邊褶皺等現象。



電動升降

方便快捷



鋁合金頂蓋

筆直而牢固




雙V型支撐系統

強力支撐幕布，使幕布平整



可旋轉固定底座


更牢固的同時更安心




黑色機箱

經典百搭






屏幕主視圖(實際投影面積在虛線內)



機箱側視圖



機箱側視圖(頂蓋尺寸)

S 常規/長焦 電動地升幕 -灰幕-									
投影區 比例	投影面積 對角尺寸	投影面積尺寸		總長度 (含電線占用空間)	頂蓋長度	屏幕總高度	包裝尺寸	毛重	淨重
	(inch)	W	H	L1	L2	Z	mm	Kgs	Kgs
16:9	72"	1594	896	1831	1670	1211	1900×240×210	24.00	23.00
	84"	1860	1046	2077	1905	1436	2150×240×210	25.00	24.00
	92"	2037	1145	2257	2081	1535	2300×240×210	26.00	25.00
	100"	2214	1245	2431	2276	1635	2500×240×210	28.00	27.00
	110"	2435	1370	2687	2528	1760	2740×240×210	31.00	30.00
	120"	2656	1494	2910	2730	1884	2970×240×210	33.00	32.00
	135"	2989	1680	3222	3041	2030	3350×240×210	37.00	36.00
	150"	3321	1867	3587	3395	2257	3650×240×210	39.00	38.00

*單位(mm)，手工制作，可能會有1-1.5mm的偏差。



Aspect Ratio	Diag.Size	Standard View Area		Overall Case Length including space occupied by plug and wire	Upper cover size	Overall Height	Packing Dimension	G.W	N.W
	(inch)	W	H	L1	L2	Z	mm	Kgs	Kgs
16:9	160"	3542	1992	3849	3652	2500	3949×260×220	50.00	40.00
16:9	170"	3763	2116	4070	3960	2600	4170×260×220	55.00	45.00
16:9	180"	3985	2241	4300	4100	2800	4300×260×220	59.00	49.00
16:9	200"	4428	2490	4700	4540	2900	4800×260×220	63.00	53.00

*單位(mm)，手工制作，可能會有1-1.5mm偏差。

! 溫馨提示，如介意以下情況請慎拍!!

1、屏幕表面能看到少許黑點、白點、污點等雜質，根據檢測方法檢測合格，則在產品合格範圍內。




圖1 側視圖

- (1) 白幕面為投影機影像的反射面（從幕面上方向下觀測為黑色面，從下方向上觀測為白色面），是觀賞影像的主功能面，故列為品質標準。白面無超出品質規格即符合出廠合格標準。
- (2) 黑面為吸收室內環境光的功能面，與影像觀賞品質無直接相關，其品質規格與白面不同。反映的輕微黑色痕跡屬於工業製成商品生產過程中不可避免的外觀現象，符合出廠合格標準。

總結：抗光投影銀幕產品黑面所見的輕微黑色痕跡以及白點等為正常的產品外觀現象，絕對不會影響影像觀賞品質，請客戶安心使用。

檢測方法：

- ① 將屏幕升起貼近牆面，觀測者直立站於距離屏幕3m遠的距離；
- ② 觀測者須在正常光照環境下（照度500—600lx）進行觀察；
- ③ 觀測者與屏幕正面距離3m觀察，且屏幕中心點須貼齊或高於水平視線（如圖1），並於中心點、向左位移1m、向右位移1m做觀察（如圖2）。

檢測結果在容許度範圍內則屬合格產品。







圖2 側視圖



2、屏幕在打開後，幕面上出現有一道道規律的淺顯摺痕，這是由於幕布長時間處於捲曲收緊狀態引起的，屬於正常現象，不影響觀影。將幕布打開，經過一段時間後，幕布上的條紋會逐漸消失。



3. 放置設備時，請確保設備始終保持水平狀態，不可將幕布傾斜或者垂直放置；
4. 屏幕在使用一段時間後，屏幕上方兩端蓋子稍微翹起屬於正常現象，不影響觀影。由於蓋子翹起，導致屏幕關閉後與罩殼有縫隙，也屬於正常現象





無線RF射頻遙控
全新遙控器，輕鬆控制畫面。



額外紅外遙控器，及紅外接收器
投影幕插上紅外遙控器，紅外遙控器就能正常工作。



電源線
屏幕供電，可拆卸電源線，方便收納。



調整桿
插入投影幕的調整孔，調整屏幕的固定高度。



Gift, No Warranty

投影幕升降無線觸發器(贈品)
插在投影機USB接口，待投影機開關電源時，自動觸發投影幕的升降。

[Read More](#)

SKU: S-VIVIDSTORM-ES-SALR-TENSION-72-120

Price: \$5600 – \$20868

分類: [電動地升幕](#)
















**適合常規/長焦投影機
戲院PVC自幕系列**



PVC自幕。電動地升幕

適合常規/長焦投影機








Technical drawings of the S-Electro-Insulator Type Spanner SPEC White Camera. The drawings include:

- Front view of screen:** Shows a square screen with dimensions 100mm (width), 100mm (height), 100mm (diagonal), and 100mm (depth).
- Side view of case:** Shows a rectangular case with dimensions 100mm (width), 100mm (height), and 100mm (depth).
- Side view of case (Top cover):** Shows a rectangular case with dimensions 100mm (width), 100mm (height), and 100mm (depth).

A small inset image shows the camera unit installed on a wall.





Aspect Ratio	Diag.Size	Standard View Area		Overall Case Length including plug and wire	Upper cover size	Overall Height	Packing Dimension	G.W	N.W
		W	H						
	(inch)	W	H	L1	L2	Z	mm	Kgs	Kgs
16:9	160"	3542	1992	3849	3652	2500	3949×260×220	50.00	40.00
16:9	170"	3763	2116	4070	3960	2600	4170×260×220	55.00	45.00
16:9	180"	3985	2241	4300	4100	2800	4300×260×220	59.00	49.00
16:9	200"	4428	2490	4700	4540	2900	4800×260×220	63.00	53.00



- 劇院PVC白幕布材質
- 在弱光環境下表現出色- 建議投影機具有1800ANSI以下的真實流明-推薦用於普通/標準/長焦投影機使用
- 電動升降-收放自如，不佔空間
- 雙彈簧V型支架系統，幕面緊繃平直
- 1.1增益，160°可視角度不挑角度，兼容3D/4K/8K高清視覺盛宴
- 4種控制方式實現上下約20-30秒！無線遙控
- 即插即用，快速安裝，無需鑽孔安裝，節省空間的設計
- 72吋-200吋可選擇 (因尺寸及重量限制，超過120吋只能送貨到樓下；72吋至120吋需要客人確認樓宇電梯能放入投影幕，及運送到指定樓層，才能安排送貨上門)
- 品牌靜音管狀電機


支援常規/長焦投影機，白幕布，支援4K投影效果，高對比度，高度還完色彩，一鍵升降，帶遙控

(如需白色機箱款，或需要135吋以上，請聯絡本店查詢 3188 4814)

VIVIDSTORM 所有專業投影幕一覽表




VIVIDSTORM
S 電動地升白幕
一鍵開啟你的次世代影院



Black Housing

Classic works


黑色機箱-常規黑邊款



Black Housing

Classic works


黑色機箱-幕布全白款



White Housing

Pure fashion

白色機箱-常規黑邊款



White Housing


Pure fashion

白色機箱-幕布全白款


更大的屏幕，更大的尺寸

屏幕尺寸：72"- 150"

根據空間大小/個人喜好
選擇合適的屏幕尺寸，
讓觀看更舒適。



推薦觀看距離：至少2.5米



S Electric Tab-Tension Floor Screen
HD White Cinema

**A More Modern Way
To Open The Screen**



無中“升”有

一鍵開啟
可收納隱藏的巨幕



屏幕打開




屏幕关上



免打孔設計 拆箱插電即用

你不需要在牆上或地板上打孔來安裝屏幕
但要確保它放在一個平坦的平面




幕平如鏡

幕面採用拉線設計，完美的呈現原始畫面，幕面無曲線波紋。

五光徘徊，十色陸離

高清白幕在夜晚關燈環境下觀影能達到最佳效果



盡收眼底，引人入勝

屏幕可選購尺寸：72"-120"



裝配品牌電機

奧科同步靜音管狀電機,運行流暢

☑ 直流供電

直流供電，節能環保

☑ 靜音設計


領先的靜音專利技術，斜齒超靜音結構設計；實現運行噪音低至30dB的靜音效果

☑ 限位調節

精準限位結構，調節理想高度

☑ 過熱保護

過熱自動斷電保護，保障電機安全健康




精彩的3D效果

在家也能享受影院級3D影像

4K高清視覺盛宴

屏幕支持4K投影(主要以投影機畫面質量為主)
暢享高清視覺盛宴



1080P




4K UHD




160°

皆“大”歡喜

全家總動員，聚會無限制，160度無死角，全景大視角。



黑色機箱
經典百搭



White Housing
Pure fashion



產品詳情

拉線工藝

屏幕搭配拉線設計，拉伸幕面更好的保證幕面平整，防止捲邊褶皺等現象。



電動升降
方便快捷




雙V型支撐系統
強力支撐幕布，使幕布平整



可旋轉固定底座
更牢固的同時更安心





S 電動地升幕 -白幕-										
投影區 比例	投影面積 對角尺寸	投影面積尺寸		總長度 (含電線占用空間)	頂蓋長度	屏幕總高度	黑布至底 (包括機箱)	包裝尺寸	毛重	淨重
	(inch)	W	H	L1	L2	Z	X	mm	Kgs	Kgs
16:9	72"	1594	896	1734	1660	1206	250	1930×240×210	24.00	23.00
	84"	1860	1046	2141	1905	1456	350	2180×240×210	25.00	24.00
	92"	2037	1145	2317	2081	1555	350	2330×240×210	26.00	25.00
	100"	2214	1245	2495	2276	1655	350	2530×240×210	28.00	27.00
	110"	2435	1370	2720	2528	1780	350	2770×240×210	31.00	30.00
	120"	2656	1494	2940	2734	1904	350	3000×240×210	33.00	32.00
	135"	2989	1680	3357	3185	2060	350	3380×240×210	37.00	36.00
	150"	3321	1867	3600	3425	2277	350	3680×240×210	39.00	38.00

*單位(mm)，手工制作，可能會有1-1.5mm的偏差。



Aspect Ratio	Diag.Size	Standard View Area		Overall Case Length including space occupied by plug and wire	Upper cover size	Overall Height	Packing Dimension	G.W	N.W
	(inch)	W	H	L1	L2	Z	mm	Kgs	Kgs
16:9	160"	3542	1992	3849	3652	2500	3949×260×220	50.00	40.00
16:9	170"	3763	2116	4070	3960	2600	4170×260×220	55.00	45.00
16:9	180"	3985	2241	4300	4100	2800	4300×260×220	59.00	49.00
16:9	200"	4428	2490	4700	4540	2900	4800×260×220	63.00	53.00

*單位(mm)，手工制作，可能會有1-1.5mm偏差。

! 溫馨提示，如介意以下情況請慎拍!!

1、屏幕表面能看到少許黑點、白點、污點等雜質，根據檢測方法檢測合格，則在產品合格範圍內。




圖1 側視圖

- (1) 白幕面為投影機影像的反射面（從幕面上方向下觀測為黑色面，從下方向上觀測為白色面），是觀賞影像的主功能面，故列為品質標準。白面無超出品質規格即符合出廠合格標準。
- (2) 黑面為吸收室內環境光的功能面，與影像觀賞品質無直接相關，其品質規格與白面不同。反映的輕微黑色痕跡屬於工業製成商品生產過程中不可避免的外觀現象，符合出廠合格標準。

總結：抗光投影銀幕產品黑面所見的輕微黑色痕跡以及白點等為正常的產品外觀現象，絕對不會影響影像觀賞品質，請客戶安心使用。

檢測方法：

- ① 將屏幕升起貼近牆面，觀測者直立站於距離屏幕3m遠的距離；
- ② 觀測者須在正常光照環境下（照度500—600lx）進行觀察；
- ③ 觀測者與屏幕正面距離3m觀察，且屏幕中心點須貼齊或高於水平視線（如圖1），並於中心點、向左位移1m、向右位移1m做觀察（如圖2）。

檢測結果在容許範圍內則屬合格產品。






圖2 側視圖




2、屏幕在打開後，幕面上出現有一道道規律的淺顯摺痕，這是由於幕布長時間處於捲曲收緊狀態引起的，屬於正常現象，不影響觀影。將幕布打開，經過一段時間後，幕布上的條紋會逐漸消失。



3. 放置設備時，請確保設備始終保持水平狀態，不可將幕布傾斜或者垂直放置；

4. 屏幕在使用一段時間後，屏幕上方兩端蓋子稍微翹起屬於正常現象，不影響觀影。由於蓋子翹起，導致屏幕關閉後與罩殼有縫隙，也屬於正常現象





無線RF射頻遙控
全新遙控器，輕鬆控制畫面。



額外紅外遙控器，及紅外接收器
投影幕插上紅外遙控器，紅外遙控器就能正常工作。



電源線
屏幕供電，可拆卸電源線，方便收納。



調整桿
插入投影幕的調整孔，調整屏幕的固定高度。



Gift, No Warranty

投影幕升降無線觸發器(贈品)
插在投影機USB接口，待投影機開關電源時，自動觸發投影幕的升降。


[Read More](#)

SKU: S-VIVIDSTORM-ES-S-TENSION-WC-72-120

Price: \$5400 – \$21088

分類: [電動地升幕](#)





快速折疊幕



AOV 4:3 快速折叠幕 多尺寸選擇 (QUICK FOLDING SCREEN)

長寬比：4:3

採用固定結構方式的銀幕。正投選用軟白幕，進口投幕布，畫質一流，紋理細膩，質地光潔柔滑，平整不變形，有良好的抗褶皺能力，配有攜帶式航空箱，方便移動無須安裝直接使用，特別適合辦公室、會議廳作簡報使用，應用範圍廣泛。

快速折叠幕



比例	規格	型號	投影面積		外罩尺寸	航空箱包裝尺寸	重量 (kg)
			W(mm)	H(mm)	LxDxH(mm)	LxDxH(mm)	
4:3	100"	FF100X	2032	1524	2184x1676x80	1260x410x440	46
	120"	FF120X	2438	1828	2590x1980x80	1460x410x440	50
	150"	FF150X	3200	2438	3200x2438x80	1500x410x470	55
	180"	FF180X	3660	2740	3810x2895x80	1630x410x470	60
	200"	FF200X	4064	3048	4216x3200x80	1780x410x470	64
	250"	FF250X	5080	3810	5272x3986x100	1530x570x620	80
	300"	FF300X	6100	4570	6305x4735x100	1690x570x620	90
	400"	FF400X	8128	6096	8365x6295x100	1930x570x620	110

快速折叠幕



比例

4:3

規格	100"
型號	FF100X
投影面積	W(mm)
	2032
投影面積	H(mm)
	1524
外罩尺寸 LxDxH(mm)	2184x1676x80
包裝尺寸 LxDxH(mm)	1260x410x440
重量 (kg)	46

規格	120"
型號	FF120X
投影面積 W(mm)	2438
H(mm)	1828
外罩尺寸 LxDxH(mm)	2590x1980x80
包裝尺寸 LxDxH(mm)	1460x410x440
重量 (kg)	50
規格	150"
型號	FF150X
投影面積 W(mm)	3200
H(mm)	2438
外罩尺寸 LxDxH(mm)	3200x2438x80
包裝尺寸 LxDxH(mm)	1500x410x470
重量 (kg)	55
規格	180"
型號	FF180X
投影面積 W(mm)	3660
H(mm)	2740
外罩尺寸 LxDxH(mm)	3810x2895x80
包裝尺寸 LxDxH(mm)	1630x410x470
重量 (kg)	60
規格	200"
型號	FF200X
投影面積 W(mm)	4064
H(mm)	3048
外罩尺寸 LxDxH(mm)	4216x3200x80
包裝尺寸 LxDxH(mm)	1780x410x470
重量 (kg)	64
規格	250"
型號	FF250X
投影面積 W(mm)	5080
H(mm)	3810
外罩尺寸 LxDxH(mm)	5272x3986x100
包裝尺寸 LxDxH(mm)	1530x570x620
重量 (kg)	80
規格	300"
型號	FF300X
投影面積 W(mm)	6100
H(mm)	4570
外罩尺寸 LxDxH(mm)	6305x4735x100

包裝尺寸 LxDxH(mm)	1690x570x620	
重量 (kg)	90	
規格	400"	
型號	FF400X	
投影面積	W(mm)	8128
	H(mm)	6096
外罩尺寸 LxDxH(mm)	8365x6295x100	
包裝尺寸 LxDxH(mm)	1930x570x620	
重量 (kg)	110	

[Read More](#)**SKU:** S-AOV-FASTFOLD**Price:** \$4180 – \$19980**分類:** [快速折疊幕](#)

INDEX

A

AOV 4

- 3 快速折叠幕 多尺寸選擇 (Quick Folding Screen) 33

V

VIVIDSTORM S-ALR 常規/長焦 抗光灰幕 電動地升幕 黑色機箱 (16
- 9) 3

VIVIDSTORM S-WC 常規/長焦 電動地升幕 白幕/黑邊/黑色機箱 (16
- 9) 14